

Datasheet Conveyor Belt




NITTA CORPORATION OF HOLLAND

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
1 RF 709 V
- **Nitta Japan code:**



Construction: 1 ply polyester, rigid, felt on top

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	Felt	PVC	Fabric	
Thickness:	1,8		-	mm (approx.)
Colour:	White	White	-	
Hardness:	-		-	
Profile:	-		-	

Total thickness:	3,1	mm (approx.)
Weight:	2,4	kg/m ² (approx.)
Max. width:	2000	mm
Belt support:	Sliderbed (Rollers), Flat	

Rating at 1% elongation:	7	N/mm
Advised pretension:	2 - 4	N/mm
Maximum allowable tension:	10	N/mm
Temperature range:	-10 to +90	°C

Minimum pulley diameters:		
Flexing:	30	mm
Backflexing:	45	mm

Special approval: FDA, 10/2011/EC + amendments

Applications:

- Conveyor belt in bakeries
- Proofer cabinets
- Excellent release of dough in bakeries
- Oil and grease resistant

Date of issue 25-04-2014-1

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.com