

Datasheet Conveyor Belt



NITTA CORPORATION OF HOLLAND

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 LRF 204
- **Nitta Japan code:**



Construction: 2 plies polyester, rigid

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	PVC	PVC	Fabric	
Thickness:	0,4		-	mm (approx.)
Colour:	Green	Green	-	
Hardness:	80 Shore A		-	
Profile:	-		-	

Total thickness: 2 mm (approx.)
Weight: 2,3 kg/m² (approx.)
Max. width: 3000 mm
Belt support: Sliderbed (Rollers), Flat

Rating at 1% elongation: 8 N/mm
Advised pretension: 4 - 7 N/mm
Maximum allowable tension: 17 N/mm
Temperature range: -10 to +80 °C

Minimum pulley diameters:
Flexing: 25 mm
Backflexing: 50 mm

Special approval: Not applicable

Applications:
 General purpose conveying
 Conveying fruit and vegetables
 Conveying of boxes in packaging lines
 Conveying of tobacco and tea

Date of issue 21-03-2014-1

Your Partner In Belting Solutions