

Datasheet Conveyor Belt




**NITTA CORPORATION
OF HOLLAND**

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:
2 MF 96 NP IM**
- **Nitta Japan code:**



Construction: 2 plies polyester, rigid

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	PVC	PVC	Impregnated fabric	
Thickness:	6		0,1	mm (approx.)
Colour:	Black	Black	Transparent	
Hardness:	80 Shore A		-	
Profile:	NP		-	

Total thickness:	8,9	mm (approx.)
Weight:	10	kg/m² (approx.)
Max. width:	2200	mm
Belt support:	Sliderbed (Rollers), Flat	
Rating at 1% elongation:	30	N/mm
Advised pretension:	12 - 20	N/mm
Maximum allowable tension:	47	N/mm
Temperature range:	-10 to +80	°C
Minimum pulley diameters:		
Flexing:	400	mm
Backflexing:	600	mm

Special approval: Not applicable

Applications: Cutting belt for marble and granite plates

Date of issue 17-03-2014-1

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.com