


Datasheet Conveyor Belt

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
3 LRWAF 901
- **Nitta Japan code:**



Construction: 3 plies polyester, rigid, antistatic

	TOP COVER	INNER LAYER	BOTTOM SIDE
Material:	Impregnated fabric	PVC	Whisper antistatic fabric
Thickness:	0,1	-	mm (approx.)
Colour:	Black	Black	-
Hardness:	-	-	-
Profile:	-	-	-

Total thickness:	3	mm (approx.)
Weight:	3,2	kg/m ² (approx.)
Max. width:	3000	mm
Belt support:	Sliderbed (Rollers), Flat	

Rating at 1% elongation:	12	N/mm
Advised pretension:	5 - 8	N/mm
Maximum allowable tension:	20	N/mm
Temperature range:	-10 to +80	°C

Minimum pulley diameters:		
Flexing:	100	mm
Backflexing:	150	mm

Special approval: Not applicable

Applications:

- Accumulation belt
- Internal transport, post offices and distribution centres
- Luggage handling in airports and passenger terminals
- For bowling lanes - Pin setters
- Conveying of (un)vulcanised rubber